

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste

ATHENS 2017

5th International Conference on
Sustainable Solid Waste



University of Córdoba
Spain

Presenting Author: Antonio López-Uceda.


A. López-Uceda, Adela P. Galvín, Jesús Ayuso,
J.R. Jiménez, T. Vanwalleghem, Adolfo Peña.

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste

ATHENS 2017




Urban and rural population of the world, 1950–2050



Reference: *World Urbanization Prospects: The 2014 Revision*. (United Nations, 2014)

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste


ATHENS 2017



RUNOFF
WATER
MITIGATION




WATER AND AIR
QUALITY
IMPROVEMENT




HEAT ISLAND
MITIGATION

THERMAL
REGULATION
OF BUILDINGS



CARBON
STORAGE



SOUND
PROOFING

Reference: Green Roof Technology

ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



University
of Córdoba
Spain



ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste




University
of Córdoba
Spain



ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



University
of Córdoba
Spain

Acinos alpinus



Bellis perennis



*Brachypodium
retusum*



Cerastium tomentosum



Dianthus arenarius



Lobularia maritima



Lotus corniculatus



Paronychia argentea



Phagnalon saxatile




Sanguisorba minor



Sedum sediforme



Trifolium repens



ATHENS 2017


Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



In Córdoba, heat peaked on 16th June (5 days ago) the highest temperature in Europe in 2017 with 43.8°C

Extreme heat across Western Europe

Insert city/postcode



Observed maximum temperatures for the Iberian Peninsular on the 16th June 2017. Credit: MeteoGroup.

Extreme heat across Western Europe

17.06.2017 17:23


If you think it's hot in the UK right now, then spare a thought for our neighbours in Iberia. Here, temperatures have been at near record levels for June, with Spain and Portugal experiencing an early summer heatwave.

Although high temperatures are normal in Spain at this time of the year – the average maximum in June for Madrid is 27C for example – the extreme temperatures that have been experienced recently are highly unusual. Madrid reached 40.5C (105F) on the 15th June. Several weather stations broke their monthly records, and the heat peaked on the 16th June, with 43.8C (111F) recorded at Córdoba Airport in south-central Spain. At least 6 provinces were put on a significant amber alert for high temperatures to climb above 40C by the Spanish meteorological agency.

Reference: <http://www.weathercast.co.uk/weather-news/>

ATHENS 2017


Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



World Construction and Demolition Waste (CDW) Production in tonnes.

ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



Commercial Vegetable
Substrate (CVS)



Fine Mixed Recycled
Aggregate (FMRA)

Bulk density
(g/cm³)


0.6

1.4

Water absorption
(%)

41.3

3.6



Depth = 10 cms.

ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



		S100	S50
<i>Fine Mixed Recycled Aggregate (FMRA)</i>			50%
<i>Commercial Vegetable Substrate (CVS)</i>		100%	50%



THE AIM:

In this **Extensive Green Roof Experiment**, among other issues, we conducted **the experimental risk assessment** of these mixes used as growing medium for vegetation.

For this purpose, we conducted a **long-term “on-site” leaching test** motivated by the Standards requested by the European Committee for Standardization (CEN / TC 292). It proposes an **on-site verification test for long-term prediction** to verify the material's behaviour, in terms of pollutants emissions, in addition to basic characterization and conformity tests.

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



The different leaching test methods used :



Compliance Test (UNE-EN 12457-3:2003)

$L/S=2; 10 \text{ l/Kg}$



Column test (NEN 7343:1994)

$L/S=0.1; 0.2; 0.5; ,1; 2; 5 \text{ l/Kg}$

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



The different leaching test methods used :



“ on-site” test carried out in the extensive green roof piece of grounds similar to column test (NEN 7343:1994)

$$L/S=0.1; 0.2; 0.5; 1; 2; 5 \text{ l/Kg}$$

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



Compliance test results and the Landfill Directive limits




Element	Landfill Directive Limits						S100		S50	
	L/S = 2			L/S = 10			L/S=2	L/S=10	L/S=2	L/S=10
	Inert≤	Non Haz	Haz	Inert≤	Non Haz.	Haz	mg/kg	mg/kg	mg/kg	mg/kg
		mg/kg			mg/kg					
As	≤0.1	0.1-0.4	0.4-6	0.5≤	0.5-2	2-25	0.013	0.067	0.010	0.027
Ba	≤7	7-30	30-100	≤20	20-100	100-300	0.370	0.839	0.136	0.378
Cd	≤0.03	0.03-0.6	0.6-3	≤0.04	0.04-1	1-5	0.000	0.000	0.000	0.001
Cr	≤0.2	0.2-4	4-25	≤0.5	0.5-10	10-70	0.011	0.033	0.070	0.130
Cu	≤0.9	0.9-25	25-50	≤2	2-50	50-100	0.019	0.032	0.013	0.025
Hg	≤0.003	0.003-0.05	0.05-0.5	≤0.01	0.01-0.2	0.2-2	0.000	0.000	0.000	0.001
Mo	≤0.3	0.3-5	5-20	≤0.5	0.5-10	10-30	0.007	0.014	0.115	0.227
Ni	≤0.2	0.2-5	5-20	≤0.4	0.4-10	10-70	0.014	0.012	0.004	0.008
Pb	≤0.2	0.2-5	5-25	≤0.5	0.5-10	10-50	0.000	0.000	0.000	0.000
Sb	≤0.02	0.02-0.2	0.2-2	≤0.06	0.06-0.7	0.7-5	0.002	0.002	0.008	0.036
Se	≤0.06	0.06-0.3	0.3-4	≤0.1	0.1-0.5	0.5-7	0.006	0.006	0.010	0.004
Zn	≤2	2-25	25-90	≤4	4-50	50-200	0.176	0.140	0.012	0.047
Chloride	≤550	550-1·10 ⁴	(1-1.7)·10 ⁴	≤800	800-1.5·10 ⁴	(1.5-2.5)·10 ⁴	2889	1617	440	500
Fluoride	≤4	4-60	60-200	≤10	10-150	150-500	<1	<5	<1	<5
Sulphate	≤560	560-1·10 ⁴	(1-2.5)·10 ⁴	≤1·10 ³	1·10 ³ -2·10 ⁴	2·10 ⁴ -5·10 ⁴	6366	9380	4110	12570

Non Haz= Non Hazardous; Haz=Hazardous

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



Compliance test results and the Landfill Directive limits




Comparison

Lab

to

on-site

CHLORIDE



Comparison

Lab




to

on-site




SULPHATE



ATHENS 2017

Experimental risk assessment of Extensive Green Roofs with fine fraction of mixed recycled aggregates from construction and demolition waste



- The 12 Mediterranean plants selected did not show any significant difference in terms of survival and cover surface respect to the mix used as growing medium for vegetation.



Conclusion:

The experimental risk assessment of extensive Green Roofs with fine fraction of MRA from CDW, here presented indicates:

→ Real application of FMRA with CVS as substrates in extensive green roofs, release less amount of sulphate and chloride anions in comparison to laboratory. It implies that the effect of laboratory conditions can overestimate the potential pollutant of these materials.

ATHENS 2017

**Experimental risk assessment of Extensive Green Roofs
with fine fraction of mixed recycled aggregates
from construction and demolition waste**



Thank you for your attention

Antonio López Uceda
p62louca@uco.es

Acknowledgements

The authors would like to express appreciation for the support of the sponsor: the Agency of Public Works of Andalusia, Spain, who funded the project: “Optimizing the potential of Green Roofs for building rehabilitation: Interaction between recycled substrates, water properties and energy efficiency” whose results are partially here presented.