



Università
Ca' Foscari
Venezia

V:
Università
degli Studi
della Campania
Luigi Vanvitelli

INNOVen
INNOVATION FOR
THE ENVIRONMENT



SPIN-OFF
DELL'UNIVERSITÀ
DEGLI STUDI DI
VERONA

NAXOS 2018

6th International Conference on Sustainable
Solid Waste Management, Naxos Island,
Greece, 13–16 June 2018

Integrated AcoD system of the organic fraction of MSW and sewage sludge: Case study

A. Piasentin¹, L. Girotto¹, G. Moretto², F. Ardolino³ & F. Cecchi*

*InnoVen srl, Spinoff University of Verona

¹Alto Trevigiano Servizi S.r.l., Montebelluna (TV)

²Department of Environmental Sciences, Informatics and Statistics, University Ca' Foscari of Venice

³Department of Environmental, Biological and Pharmaceutical Sciences and Technologies, University of Campania "Luigi Vanvitelli"



SPIN-OFF
DELL'UNIVERSITÀ
DEGLI STUDI DI
VERONA

Contents

1. Introduction



- AcoD system overview
- Feasible routes for OFMSW recovery
- AcoD integration within existing WWTPs

2. Materials and Methods

- Case study presentation
- Mixtures characterization
- Steady state conditions operating parameters
- Steady state conditions performance parameters
- Energy considerations
- Preliminary LCA study

3. Conclusions


ACoD: as territory service was discussed in the 2th IC-SSWM according to the following schemes



Two main objectives for OFMSW recovery and valorisation through AcoD:

1 Maximisation of energy recovery

2 Maximisation of matter recovery




The choice is driven by territory diversity and available technologies



Case Study Approach

Screw press flowchart



- Squeezed wet biowaste contains approx. 15-20% TS
- This approach could favour ACoD with SS in nearby WWTPs

Case study: full-scale implementation of OFMSW-SS AcoD Treviso WWTP

Squeezed OFMSW from door-to-door separate collection ensures high quality organic waste



Parameter	Mean ± St. Dev.	Max	Min
TS, g/kg	135 ± 52	211.0	33.2
TVS, g/kg	113 ± 44	176.6	24.9
TVS/TS, %	84 ± 3	97	75

Organic waste recycling in
Treviso Province = **85.3%**
(ARPAV, 2017)



VERONA UNIVERSITÀ
DELL'UNIVERSITÀ
DEGLI STUDI DI
VERONA

SPIN-OFF
DELL'UNIVERSITÀ
DEGLI STUDI DI
VERONA

Case study: full-scale implementation of OFMSW-SS AcoD Treviso WWTP



ALTO TREVIGIANO SERVIZI

- **Treviso (TV)**

A.T.S. S.r.l. WWTP



Feedstock mixture characterization

Parameter	Mean ± St. Dev.	Max	Min
TS, g/kg	33.8 ± 5.3	48.9	19.4
TVS, g/kg	24.9 ± 3.8	34.9	13.8
TVS/TS, %	74 ± 4	88	55
pH	5.4 ± 0.25	5.92	5.08
COD, gCOD/kgTS	811 ± 52	979	693
TKN, gN/kgTS	41.3 ± 6.2	48.9	19.2
P _{org} , gP/kgTS	11.0 ± 3.1	20.0	4.8



Effluent characterization


Parameter	Mean ± St. Dev.	Max	Min
TS, g/kg	18 ± 2.7	28.0	13.5
TVS, g/kg	12.1 ± 2.3	19.0	8.0
TVS/TS, %	67 ± 7	88	52
COD, gCOD/kgTS	736 ± 53	906	648
TKN, gN/kgTS	40.0 ± 8.1	49.1	19.1
P _{org} , gP/kgTS	13.7 ± 3.7	27.1	9.1

2000 m³ anaerobic digester
 CSTR



Steady state conditions operating parameters

Hydraulic Retention Time




During steady state conditions an average **HRT = 20 days** was maintained




Parameters of steady state operating conditions

OFMSW flow rate fed to digester




Sludge flow rate fed to digester





Parameters of steady state operating conditions

Organic Loading Rate




- Average OFMSW OLR = 0.7 kgVS/m³d
- Average Sludge OLR = 1.1 kgVS/m³d

*All results shown are related to steady state conditions and based on an average of 20 days
Steady state conditions cover a time period from 22/04/17 to 28/02/18




Steady state conditions performance parameters

Biogas production




Biogas main composition







Steady state conditions performance parameters

Specific Gas Production



Stable SGP was observed with an average value of **0,5 m^3/kgVSd**


Steady state conditions: process stability parameters



Parameter	Mean ± St. Dev.	Max	Min
pH	7.4 ± 0.19	7.7	7.1
Alk pH6, mgCaCO ₃ /l	2015 ± 258	2326	1387
Alk pH4, mgCaCO ₃ /l	2932 ± 290	3208	2303
N-NH ₄ ⁺ , mgN-NH ₄ ⁺ /l	530 ± 84	726	365
VFA, mgCOD/l	58 ± 23	232	0

Steady state conditions were characterized by stable pH, alkalinity, ammonium and VFA concentrations

Energy consumption and recovery




- Electric energy is autoproduced through a $185 \text{ kW}_{\text{el}}$ CHP motor
- Energy produced accounts for **50% of the total plant energy demand**

Preliminary LCA study

Two different LCA scenarios: **past scenario** **VS** **present scenario**


- **Past scenario:** OFMSW composting



Preliminary LCA study

Two different LCA scenarios: **past scenario** VS **present scenario**

- **Present scenario:** OFMSW pretreatment → AcoD + Composting





Preliminary LCA study

	"Past" scenario		"Present" scenario		Delta (Present-Past)	
	Specific electrical consumption, kWh/t _{IN}	Input, t _{IN} /d	Electrical consumption, kWh/d	Input, t _{IN} /d	Electrical consumption, kWh/d	
Composting Wastewater line	69 0.04	138 180000	9515 6667	129 180000	8880 6667	-635 0
	Recovered EE, kWh/t _{Biogas to CHP}	Biogas to CHP, t _{IN} /d	Recovered EE, kWh/d	Biogas a CHP, t _{IN} /d	Recovered EE, kWh/d	Recovered EE, kWh/d
Recovered EE from CHP	1771	-	-	1.89	3345	3345
Total electrical consumption			kWh/d 16182		kWh/d 12202	kWh/d -3979

Global Warming Potential of the Italian electrical mix:

0.437 kg CO₂ eq for the production of 1 kWh (from: IPPC 2001 500a, and IEA 2016)

Potential avoided GWP: 1739 kg CO₂ eq. per day


Conclusions

OFMSW codigestion with SS ensures:

- **Valorisation of organic wastes through energy recovery**
- **Best territorial service for citizens**
- **Simple operational work**
- **Stable operating condition under SSC**
- **Higher revenues**
- **Slight increase in sludge production**
- **High energy savings due to CHP biogas conversion**
- **Undeniable overall convenience in terms of LCA**

Applicable to any WWTP with reduced upgrading costs

Naxos 2018
6th IC - SSWM
13 – 16 June 2018



THANK YOU FOR YOUR ATTENTION!