

Danish BAT for hospital wastewater treatment - Full scale treatment of hospital wastewater consisting of MBR, ozone and GAC

Ulf Nielsen, P. E. Jørgensen, M. M. Klausen, J. Søholm, J. Tuerk
SWWS Athens, 15.09.2016

Full scale test plant at a large university hospital

Herlev University hospital

- 850 beds
- All major clinical specialities (cancer etc.)
- Water consumption: 170.000 m³/y



Full scale test treatment plant

- Constructed in 2013-14. Operated since May 2014
- Full solution with **water, air and sludge treatment**
- Private-Public innovation Partnership (PPP)






Setup of the treatment plant



Membrane BioReactor (MBR) plus two test lines for polishing :

Sample points: ●



Overview of treatment plant



Process tanks

Polishing lines

1. GAC + Ozone + UV
2. Ozone + GAC + UV




Ceramic membrane filtration

Sludge drying to 80% dry matter

Sludge bags and screenings for incineration
Pick-up 2/wk
District heating produced


Air treatment for odour/pathogen removal using photoionization (UV+GAC)

Test period and plan




Results - COD

Stable removal



Efficient removal of pharmaceuticals (API's)

Most efficient setup: MBR-Ozone-GAC (Line 2)



API's measured below $PNEC_{\text{Freshwater}}$ or LOD in effluent

Ratio
 $MEC/PNEC_{\text{Freshwater}}$
in the brackets

| Influent | | After MBR | | Effluent | |
|---------------------------------------|--|--|--|---|--|
| Atorvastatin (0.6 - 6.5) | | Azithromycin (2.3 - 8.1) | | No pharmaceuticals exceeding $PNEC_{\text{Freshwater}}$ | |
| Azithromycin (2.8 - 21) | | Carbamazepine (0.7 - 1.3) | | | |
| Capsaicin (0.1 - 11) | | Cefalexin (LOD - 3.2) | | | |
| Carbamazepine (LOD - 2.0) | | Ciprofloxacin (4.6 - 93) | | | |
| Cefalexin (LOD - 8.4) | | Clarithromycin (2.2 - 10) | | | |
| Ciprofloxacin (20 - 303) | | Diclofenac (4.2 - 11) | | | |
| Clarithromycin (1.7 - 130) | | Erythromycin (0.3 - 1.1) | | | |
| Diclofenac ((3.0 - 11) | | Iomeprol (LOD - 1.0) | | | |
| Erythromycin (0.3 - 26) | | N4-Acetyl-Sulfamethoxazole (0.4 - 1.9) | | | |
| Ibuprofen (1.5 - 13) | | Ofloxacin (LOD - 1.5) | | | |
| Iomeprol (0.2 - 5) | | Sulfamethoxazole (11 - 64) | | | |
| Metonidazole (LOD - 2.1) | | Tramadol (1.2 - 2.0) | | | |
| N4-Acetyl-Sulfamethoxazole (15 - 108) | | Venlafaxine (5.2 - 7.7) | | | |
| Ofloxacin (LOD - 3.3) | | Zopiclone (0.6 - 4.7) | | | |
| Paracetamol (6.5 - 87) | | | | | |
| Prednisolon (LOD - 16) | | | | | |
| Sulfamethoxazole (21 - 133) | | | | | |
| Sulfapyridin (0.1 - 3.7) | | | | | |
| Tramadol (LOD - 4.2) | | | | | |
| Venlafaxine (2.5 - 11) | | | | | |
| Zopiclone (LOD - 5.3) | | | | | |


No API's
measured above
PNEC

14 API's measured
above PNEC

21 API's measured
above PNEC



Indicator substances measured in effluent

Measured below PNEC_{Freshwater}



The polishing process that comes first removes most MBR-Ozone-GAC (Line 2) gives the best total removal


June 10
2015




**No bromate
formation after
ozonation (< 2 µg/l)**
WHO guideline (2005): 10 µg/l

Lower ozone dosages gives significantly less removal by ozone

Line 1
MBR **GAC** **O₃**
5 mg O₃/l \approx 1 mg O₃/mg DOC



Line 2
MBR **O₃** **GAC**
7 mg O₃/l \approx 1 mg O₃/mg DOC




**June 11
2015**

MBR membrane leakage control system



Online *E. Coli* monitoring in the permeate

- Ceramic 200 nm pore size membranes
- If no *E. Coli* in the permeate – no leakage!
- Online monitoring of *E. Coli* specific enzyme activity (Beta-glucoronidase) – controlled by growth tests (IDEXX)
- Monitored every 15-30 minutes (LOD: 20-100 MPN/100 ML)



Energy and economy

- Total operating and maintenance costs: 1.45 EURO/m³
- Total investment cost: 3.3-4.7m EURO (new plant)



Simpler pay back period, saving the sewer-tax:

4 m EURO/0.4m EURO/y = 10 years

Yearly savings: 200.000 m³/year*15 DKK(25,54-10.87) = 3 mio DKK/year ~ 0.4m EURO/year

Conclusions (1)

- The plant is now considered as BAT for treatment of hospital wastewater in Denmark
- The **MBR-Ozone-GAC** sequence is the most efficient setup
- All monitored API's in the outlet are **below PNEC or LOD**
- An efficient **membrane leakage control system** developed
- Ozone-dosage around **3.5 mg/mg DOC gives the best removal**. No critical bromate formation is seen.
- 1/3 of the GAC filters have been changed per year in the two years operation period. **Breakthrough of API's does not seem to be critical within this change interval**

Conclusions(2) and next steps

- Total operation and maintenance costs **1.45 EURO/m³**

Next steps 2016-2017:

- The treated water will be discharged to the local stream
- 10.000 m³/year will be reused as cooling water at the hospital



Thanks for your attention!

Funding:

The Market Development Fund



**Herlev
Hospital**



COPENHAGEN
Welcome to Denmark



Herlev
Kommune



BIOFOS

Cooperation partners:



Contact:

Ulf Nielsen, DHI uln@dhigroup.com

Cell: +45 6162 7277

Conclusions on treatment efficiency

| Parameters | Raw untreated wastewater | Treated wastewater |
|---|---|--|
| Toxic and persistent antibiotics (ciprofloxacin, clarithromycin and sulfamethoxazole) and painkiller (diclofenac) | Factor 10-180 exceedings of effect limits (PNEC) for water living organisms | No exceedings of effect limits (PNEC) for water living organisms |
| Contrast media (e.g. iomeprol) | High concentration (2,5-7 mg/l) | 99 % removal |
| Antibiotic resistant bacterium | High occurrence of multi resistant bacterium | No fecal or multi resistant bacteria |
| Fish fry (zebra fish) | 100 % mortality within 96 hours | 0 % mortality within 96 timer |
| Crustacean (daphnies) | No offsprings (all test animals died) | Offsprings survives as in clean water controls |
| Estrogenic activity | Estrogen effects | No estrogen effects |